

ODE-3-140041-3F1A

Optidrive E3 VFD Datasheet

1.5 kW (2 HP), 4.1 A, 380-480 V, 3PH

IP66 Outdoor Non-switched Variable Frequency Drive with EMC Filter



Input Ratings

| | |
|-----------------------------|-----------|
| Supply Voltage | 380-480 V |
| Input Phases | 3 |
| Supply Current Continuous | 5.6 A |
| Supply Fuse or MCB (Type B) | 10 A |

Output Ratings

| | |
|---------------------|--------------------|
| Motor Output Rating | 1.5 kW (2 HP) |
| Output Voltage | 0 – Supply Voltage |
| Output Current | 4.1 A |

Cable Information

| | |
|------------------------|--------------------------------|
| Max Supply Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Length | 100 m (328 ft) |

Factory Build Options

| | |
|------------------|------------------------------|
| EMC Filter | Internal EMC Filter |
| Brake Transistor | No Internal Brake Transistor |
| Enclosure | IP66 Outdoor Non-switched |
| Display | LED |
| PCB Coating | - |

Dimensions

| | |
|---------|-------------------|
| Size | 1 |
| Height | 232 mm (9.13 in) |
| Width | 161 mm (6.34 in) |
| Depth | 152 mm (5.98 in) |
| Weight | 2.3 kg (5.07 lbs) |
| Fixings | 4 x M4 |

Packaged Dimensions


| | |
|--------|-------------------|
| Height | 205 mm (8.07 in) |
| Width | 210 mm (8.27 in) |
| Depth | 345 mm (13.58 in) |
| Weight | 2.9 kg (6.39 lbs) |




 **Buy this drive or get more information**
Find your local sales partner on invertekdrives.com



How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions



Buy this drive or get more information

Find your local sales partner on
invertekdrives.com

